Jan 518, 423

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



Rec'd PCT/PTO 17 DEC 2004

(43) International Publication Date 24 December 2003 (24.12.2003)

PCT

(10) International Publication Number WO 03/105673 A2

(51) International Patent Classification7:

(21) International Application Number:

17 June 2003 (17.06.2003) (22) International Filing Date:

(25) Filing Language:

English

A61B

PCT/US03/19150

(26) Publication Language:

English

(30) Priority Data: 60/389,365

17 June 2002 (17.06.2002)

(71) Applicant (for all designated States except US): TRIM-EDYNE, INC. [US/US]; 15091 Bake Parkway, P.O. Box 57001, Irvine, CA 92618 (US).

(72) Inventors; and

RICHLEY, (75) Inventors/Applicants (for US only): Richard, R. [US/US]; 3434 Midway Drive, Suite 2001, San Diego, CA 92110 (US). LOEB, Marvin, P. [US/US]; 2872 Coast Circle, Apt. 101, Huntington Beach, CA 92649 (US).


- Agents: CEPURITIS, Talivaldis et al.; Olson & Hierl, (74)Ltd., 20 North Wacker Drive, 36th Floor, Chicago, IL 60606 (US). (81) Designated States (national): AE, AG, AL, AM, AT, AU,
- AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: DEVICES AND METHODS FOR MINIMALLY INVASIVE TREATMENT OF DEGENERATED SPINAL DISCS



(57) Abstract: Spinal stabilization devices and their methods of insertion and use to treat degenerated lumbar, thoracic or cervical spinal discs in minimally invasive, outpatient procedures are described. In one embodiment, the spinal stabilization device is an expandable cage made of a coil or perforated cylindrical tube with a bulbous or bullet-shaped distal end and a flat or rounded proximal end. In a preferred embodiment, the spinal stabilization device is mechanically expanded to a larger diameter or is made of a superelastic nickel-titanium alloy which is thermally programmed to expand to a relatively larger diameter when a pre-determined transition temperature below body temperature is reached. To treat a degenerated disc, a guide wire is inserted into the disc and an endoscope is inserted through a posterolateral puncture in the back and advanced up to the facet of the spine. Mechanical tools or laser energy, under endoscopic visualization, are used to remove or vaporize a portion of the facet bone, creating an opening into the foraminal space in the spine for insertion of an endoscope, which enables the disc, vertebra and nerves to be seen. The passageway is expanded, mechanical tools or laser of RF energy are used to make a tunnel into the disc, and a delivery cannula is inserted up to the opening of the tunnel. An insertion tool is used to insert one or more spinal stabilization devices into the tunnel in the disc, preserving the mobility of the spine, while maintaining the proper space between the vertebra. Laser or radio frequency (RF) energy is used to coagulate bleeding, vaporize or remove debris and shrink the annulus of the disc to close, at least partially, the tunnel made in the disc.